

SPECIFICATION SHEET

VERSION VERSION DATE 04/02/21 **PRINT DATE** 25/04/24

PRODUCT LINOLEATE D'ETHYLE

APPLICATIONS Industrial raw material not intended for direct use. **IUPAC NAME** CIS,CIS-9,12-OCTADECADIENOATE ETHYL

SYNONYMS ETHYL LINOLATE, ETHYL CIS, CIS-9, 12-OCTADECADIENOATE

FORMULA C₂₀ H₃₆ O₂ **MOLECULAR WEIGHT** 308.5 **CAS** 544-35-4 208-868-4 **EINECS**

FEMA

CoF 711c

TARIFF NUMBER 2916150000

SPECIFICATIONS

MOBILE LIQUID (TURBID AT LOW TEMPERATURES)/SOLID ASPECT AT 20°C

COLOUR **COLORLESS TO YELLOW**

ODOUR OILY DENSITY AT 20°C (g / ml) 0,865-0,890

DENSITY 25/25

REFRACTIVE INDEX nD20 1,4450-1,4650

REFRACTIVE INDEX nD25 OPTICAL ROTATION (°)

BOILING POINT (°C) 224°C APPROX. (17 mm Hg)

MELTING POINT (°C) FLASH POINT (°C) 101 ASSAY (% GC) > 50

SOLUBILITY INSOLUBLE IN WATER VAPOUR PRESSURE **NOT DETERMINED** OTHER SOLUBILITIES **SOLUBLE IN ETHANOL**

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

SOLID MATTER CAN APPEAR, OR TURBID PRODUCT WITH COLD. HEAT GENTLY AND/OR FILTER IF NECESSARY.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.